



JUP Conference, 10-11 Jan 2002
Hosted by Princeton University

Quantitative Experimental Results: Automation to Support Time- Critical Replanning Decisions

Kip Johnson, MIT Dept. of Aero/Astro Eng
Advisor Jim Kuchar, along with Dr. Charles Oman
Sponsored by Office of Naval Research

Disclaimer: The views expressed in this presentation are those of the authors and do not reflect the official policy or position of the U.S. Air Force, Department of Defense, or the U.S. Government.

Time-Critical Decision-Making

ie. Combat flight route planning

- Aviation, medicine, chemical and energy production, finances

Complex Problem


- Unstructured aspects
- Multiple competing interests and goals
- Time pressures

Automation Integration


- Cannot “see” everything (sensor limitations)
- Human may not understand basis for automated decisions

Experimental Goal

Discover the relationship between **time pressures**, **automation assistance**, and the resulting **decision performance**, both quantitatively and subjectively.



Replanning Task Description



Experimental Protocol

1. View Preplanned Mission


2. Change in Environment

- Hazard, Time to Target, or Fuel Update

3. Route Suggested with Varying Automation Assistance (**BLUE**)

4. Subject Modifies Flight Route Under Time Pressure

- Minimize Threat Exposure and Time to Target Deviation
- Meet Time to Target and Fuel Constraints



Independent Variables

Automation Categories

None: No Automation

- original route remains

Time/Fuel: Constraint Information Only

- meets time to target & fuel constraints

Hazard: Hazard Information Only

- avoids/minimizes hazard exposure

Full: Integration of Constraint + Hazard Information

- minimizes hazard exposure + meets constraints

Time Pressure

- 20, 28, 40, 55 seconds (logarithmic)
 - capture performance change
- Unlimited time to find individual's optimal performance

Dependent Variables

1. Quantitative human performance measured by route cost at end of time pressure.

Cost = Hazard Exposure (linear) + Time to Target Deviation (exponential)

$$Cost_{Route} = \ln \left\langle A \left[\sum_1^{\#colors} (Length_{RouteSegment} * Cost_{Color}) \right] + B \left[a_1 * \left(\exp \left(b_1 * \left| \frac{t}{t_0} \right| \right) - 1 \right) \right] \right\rangle$$

Fuel = constraint

2. Subjective evaluations.

Test Conditions

- 14 subjects: students, ave age = 25, 3 pilots, 3 females
- 3 hrs: 2 hr training, 1 hr data collection

Test Matrix:


		Time Pressure			
		20	28	40	55
Auto Category	None	M1	M2	M3	M4
	ToT/Fuel	M2	M1	M4	M3
	Hazard	M3	M4	M1	M2
	Full	M4	M3	M2	M1

- Greco-Latin Square Design
- 4 base maps (M), each rotated for 16 effective scenarios

Quantitative Analysis


Automation Effects

- Repeated Measures ANOVA
- Full auto assistance is sig. best
- Hazard auto assistance is sig. better than none




Time Pressure Effects

- Repeated Measures ANOVA
- No sig. performance improvement after \cong 28 sec



Quantitative Analysis (3)


Interaction Effects



- Only none had sig. improvement with time
- Hazard better than none and time/fuel < 55 sec, sig. at 40 sec
- None outperforms hazard and time/fuel at 55 sec, while is the worst at 20 sec
- Performance decreases at times dependent on auto level


Temporal Benefit of Automation

- Idea of “Characteristic Time” (CT)
 - Period of *beneficial* time from having auto assistance
- Possible linear metric
 - Similar slopes
 - Intercept quantifies relative auto benefit
- $CT_{Full} > 55 \text{ sec}$
- $CT_{Hazard} \cong 55 \text{ sec}$
- $CT_{Time/Fuel} \leq 20 \text{ sec}$



Failure Analysis

- Only 1 subject was perfect
- 14.3% failure rate, 32 of 224



A failed scenario had ≥ 1 of the following:

- 1. Hit a brown hazard*
- 2. Arrived target outside of time window*
- 3. Not enough fuel to complete mission*

- Most failures with hazard
 - Contrary to quantitative performance
- 40 sec had fewest failures
 - While no quantitative improvement in performance after 28 sec
- Failures at 55 sec \cong 20 sec

Failure Count	Time				
Automation	20	28	40	55	Grand Total
None	2	1	1	2	6
ToT & Fuel	0	3	2	3	8
Hazard	6	2	0	5	13
Full	2	1	1	1	5
Grand Total	10	7	4	11	32

Conclusions

- Automation does assist in time-critical decision making
 - Auto benefit decreases as available time increases
 - Auto benefit increases dependent on type and amount of information integrated by automation
- Moderate amounts of time may actually hinder performance over less time
- Subject data supported quantitative analysis

Future Work

- Develop a generalized model for decision support automation
- Identify information support needs of human
- Follow-on experiment
 - More specific to flight environment
 - Data points > 55 seconds to reach characteristic time
 - Further test interactions between partial and no automation